

# INFINA<sup>®</sup> RUN LENGTH CONFIGURATOR

CUSTOMER \_\_\_\_\_

PURCHASE ORDER NO. \_\_\_\_\_ DATE \_\_\_\_\_

## 1 SELECT MODEL / APPLICATION

### DL-AC-FLEX2-BEAM

INFINA<sup>®</sup> FLEXIBLE LINEAR WITH OPTICS

☐ 1010 10° BEAM ☐ 3030 30° BEAM ☐ ASY45 45° ASYMMETRIC

Select all that apply

☐ INDOOR  
☐ OUTDOOR  
☐ FACE DOWN



Intertek

## 2 COLOR TEMPERATURE

-27  
2700K  
-30  
3000K  
-35  
3500K  
-40  
4000K  
-50  
5000K



Some CCT may have longer lead time, consult with factory

## 3 MOUNTING OPTIONS

### MOUNTING CLIPS

☐ -MC Plastic Mounting U Clip

APPLICATIONS WITH MOUNTING CLIP  
1 (MC) is required every 6 inches

**CHANNELS** Channels<sup>1</sup> are recommended for face down or vertical applications. Lens cover is not suitable for outdoor applications. Parts with identical color block work together.

☐ A Metal Channel (-CH4M22)

☐ A 1mm Clear Lens (-CH6M22-L01)

☐ A 30°/60°/90° Adj. CH Clip (-ADJBR-L)


☐ A CH Metal Clip (-CH4M22-MCM)

## 4 RUN LENGTH

**MULTIPLE SECTIONS** linked with CC cables. Continuous run more than 33ft required an I joint Connector

**For every 5 Feet of connecting cable** - add 1 linear foot of FLEX2 strip to calculate the overall max run.

Example: 80 feet of FLEX2 strip + 15 feet of connecting cables (+3 linear feet) = 83 feet overall length



QTY	TYPE	INPUT	SECTION A	LINK/END	SECTION B	LINK/END	SECTION C	LINK/END	SECTION D	LINK/END
			FT IN		FT IN		FT IN		FT IN	
			FT IN		FT IN		FT IN		FT IN	
			FT IN		FT IN		FT IN		FT IN	
			FT IN		FT IN		FT IN		FT IN	
			FT IN		FT IN		FT IN		FT IN	
			FT IN		FT IN		FT IN		FT IN	
			FT IN		FT IN		FT IN		FT IN	
			FT IN		FT IN		FT IN		FT IN	
			FT IN		FT IN		FT IN		FT IN	

<sup>1</sup> See spec sheet for specific channels for face down applications