

# INFINA® RUN LENGTH CONFIGURATOR

CUSTOMER \_\_\_\_\_  
PURCHASE ORDER NO. \_\_\_\_\_ DATE \_\_\_\_\_

## 1 APPLICATION

### DL-AC-FLEX2-DTW-FR

INFINA Dim-to-Warm Flexible Linear with Frosted Jacket

Select all that apply

- ☐ INDOOR  
☐ OUTDOOR  
☐ FACE DOWN



## 2 COLOR TEMPERATURE



## 3 MOUNTING OPTIONS

### MOUNTING CLIPS

- ☐ -MC Plastic Mounting U Clip  
☐ -MC-HW\* Mounting Clip  
\* FOR HARDWIRE APPLICATIONS ONLY

APPLICATIONS WITH MOUNTING CLIP 1 (MC-HW) and/or 1 (MC) is required every 6 inches

### CHANNELS


Channels<sup>1</sup> are recommended for face down or vertical applications. Lens cover is not suitable for outdoor applications. Parts with identical color block & letter work together.

- |   |  |
|---|--|
| <b>A</b> Plastic Channel (-CH4)         | <b>A</b> CH4 Inner Clip (SG-MC-V)            |
| <b>B</b> Plastic Channel (-CH6Z)        | <b>B</b> CH6Z 45° Clip (SG-MC-45)            |
| <b>C</b> Metal Channel (-CH6M12)        | <b>D</b> Dead Endcap (-CH6M27-DEC)           |
| <b>C</b> 1mm Lens (-CH6M12)             | <b>D</b> Live Endcap (-CH6M27-LEC)           |
| <b>D</b> Metal Channel (-CH6M27)        | <b>D</b> CH Metal Clip (-CH6M27-MCM)         |
| <b>D</b> 11mm Lens (-CH6M27-11)         | <b>D</b> CH Adj. Clip (-CH6M27-MCMADJ)       |
| <b>E</b> Metal Channel (-CH6M20)        | <b>E</b> 30°/60°/90° Adj. CH Clip (-ADJBR-L) |
| <b>EF</b> 1mm Lens (-CH6M20/CH6M35-45)  | <b>E</b> CH Endcap Set (-CH6M20-ECS)         |
| <b>F</b> 45° Metal Channel (-CH6M35-45) | <b>F</b> CH Endcap Set (-CH6M35-45-ECS)      |
|   | <b>F</b> 45° CH Metal Clip (-CH6M35-MC)      |

## 4 RUN LENGTH

**MULTIPLE SECTIONS** linked with CC cables.

**For every 5 Feet of connecting cable** - add 1 linear foot of FLEX2 strip to calculate the overall max run.  
Example: 80 feet of FLEX2 strip + 15 feet of connecting cables (+3 linear feet) = 83 feet overall length



QTY	TYPE	INPUT	SECTION A		LINK/END	SECTION B		LINK/END	SECTION C		LINK/END	SECTION D		LINK/END
			FT	IN		FT	IN		FT	IN		FT	IN	
			FT	IN		FT	IN		FT	IN		FT	IN	
			FT	IN		FT	IN		FT	IN		FT	IN	
			FT	IN		FT	IN		FT	IN		FT	IN	
			FT	IN		FT	IN		FT	IN		FT	IN	
			FT	IN		FT	IN		FT	IN		FT	IN	
			FT	IN		FT	IN		FT	IN		FT	IN	
			FT	IN		FT	IN		FT	IN		FT	IN	
			FT	IN		FT	IN		FT	IN		FT	IN	
			FT	IN		FT	IN		FT	IN		FT	IN	

<sup>1</sup> See spec sheet for specific channels for face down applications