

INFINA[®] RUN LENGTH CONFIGURATOR

CUSTOMER _____

PURCHASE ORDER NO. _____ DATE _____

1 SELECT MODEL / APPLICATION

DL-AC-FLEX2-EB

INFINA BASIC FLEXIBLE LINEAR CLEAR JACKET

Select all that apply

- ☐ INDOOR
- ☐ OUTDOOR
- ☐ FACE DOWN



2 COLOR TEMPERATURE

-27
2700K
-30
3000K
-35
3500K
-40
4000K
-50
5000K



Some CCT may have longer lead time, consult with factory

3 MOUNTING OPTIONS

MOUNTING CLIPS

- ☐ -MC
Plastic Mounting U Clip
- ☐ -MC-HW*
Mounting Clip
- * FOR HARDWIRE APPLICATIONS ONLY

APPLICATIONS WITH MOUNTING CLIP
1 (MC-HW) and/or 1 (MC) is
required every 6 inches

CHANNELS Channels¹ are recommended for face down or vertical applications.
Lens cover is not suitable for outdoor applications.
Parts with identical color block work together.


- A** Plastic Channel (-CH6P)
- B** Metal Channel (-CH6M19)
- B** 1mm Lens (-CH6M19-L01)
- B** 11mm Lens (-CH6M19-L11)
- C** Metal Channel (-CH6M08)
- B** CH Metal Clip (-CH6M19-MCM)
- B** CH Adj. Clip (-CH6M19-MCMADJ)

4 RUN LENGTH

MULTIPLE SECTIONS linked with CC cables.

For every 5 Feet of connecting cable - add 1 linear foot of FLEX2 strip to calculate the overall max run.

Example: 80 feet of FLEX2 strip + 15 feet of connecting cables (+3 linear feet) = 83 feet overall length



QTY	TYPE	INPUT	SECTION A	LINK/END	SECTION B	LINK/END	SECTION C	LINK/END	SECTION D	LINK/END
			FT		FT		FT		FT	
			FT		FT		FT		FT	
			FT		FT		FT		FT	
			FT		FT		FT		FT	
			FT		FT		FT		FT	
			FT		FT		FT		FT	
			FT		FT		FT		FT	
			FT		FT		FT		FT	
			FT		FT		FT		FT	

¹ See spec sheet for specific channels for face down applications