



# CM401 CLASSIC SQUARE

Ceiling Fixture or ADA Sconce  
With Acrylic Shade  
Line Voltage LED Fixture

Type	
Project	
Catalog No.	



## DESCRIPTION

The CM401 series is the next generation of residential and commercial fixtures incorporating *JESCO's exclusive Driverless AC LED* technology. Operating directly off of AC voltage, no secondary LED driver is required. The square, impact resistant, acrylic lens is available in either 11" or 14" dimensions. The 11" fixture incorporates a 15W LED module which emits up to 1070 lumens from the fixture providing a similar lumen output to a 75W incandescent lamp. The 14" uses a 23W LED module emitting 1500 lumens from the fixture providing a similar light output to a 100W incandescent lamp. Both fixtures can be dimmed by most standard incandescent, electronic or magnetic low voltage, and CFL/LED dimmers. Operating at 277 VAC can be accomplished with an additional transformer.

## FEATURES

- Up to 1500 lumens emitted from fixture
- JESCO's exclusive *Driverless AC LED* technology eliminates the need for an in-line or secondary LED driver. Incorporated with our advanced heat sink design, the fixture provides superior thermal management for true 50,000 hours of operation with 70% lumen maintenance
- Patent pending inrush current / surge protection designed to prevent damage to both LED module and dimmer
- 90 CRI available in all color temperatures
- Available in 2700K, 3000K and 4000K
- Dimmable 10-100% with most leading or trailing edge incandescent or low voltage dimmers
- ADA compliant wall sconce
- Suitable for use in closet applications
- Eco Friendly – No mercury or hazardous material

## SPECIFICATIONS

<b>Model</b>	CM401-S-xx-WH		CM401-M-xx-WH	
<b>Description</b>	LED Ceiling Fixture or ADA Sconce			
<b>Input Voltage</b>	120 VAC			
<b>Wattage</b>	15W		23W	
<b>CCT</b>	3000K 4000K	2700K+	3000K 4000K	2700K+
<b>CRI</b>	80+*	90	80+*	90
<b>Lumens</b>	976Lm 1070Lm	880Lm	1369Lm 1500Lm	1230Lm
<b>Efficacy*</b>	65.1Lm/W 71.3Lm/W	58.7 Lm/W	59.5Lm/W 65.2Lm/W	53.5 Lm/W
<b>Power Factor</b>	>0.90			
<b>Dimming**</b>	10-100% Triac, ELV, MLV, CFL/LED			
<b>Dimensions***</b>	11" x 11" x 2 1/2"		14" x 14" x 3"	
<b>L<sub>70</sub></b>	50,000 hours			
<b>Finish</b>	White			
<b>Environment</b>	Indoor - Dry			
<b>Certifications</b>				
<b>Warranty</b>	5 Years – see published warranty terms for detailed information			

\*90 CRI available. Contact factory for details.



\*\*Recommended:  
- Thirty 15W or twenty 23W fixture maximum run on one 600W dimmer  
- Fifteen 15W or ten 23W fixture maximum run on one 300W dimmer  
See reverse side for recommended list of dimmers  
\*\*\* Dimensions on reverse side

## ORDERING INSTRUCTIONS

<b>MODEL</b>	<b>SHAPE</b>	-	<b>SIZE</b>	-	<b>CCT</b>	-	<b>FINISH</b>
CM	401	-		-		-	WH
CM – Series	401 – Square		S – 11" M – 14"		30 – 3000K 40 – 4000K 27 – 2700K+		WH – White

Example: **CM401-M-30-WH**

† Contact factory for details



www.jescolighting.com  
support@jescolighting.com  
Tech Support: 855.592.0029

15 Harbor Park Drive  
Port Washington, NY 11050  
Main Line: 800.527.7796  
Fax Line: 855.265.5768

219 South 6<sup>th</sup> Ave  
City of Industry, CA 91746  
Main Line: 855.654.0110  
Fax Line: 626.333.2955

Rev 11  
7/28/2017

Specifications subject to change without notice.





# CM401 CLASSIC SQUARE

Ceiling Fixture or ADA Sconce  
With Acrylic Shade  
Line Voltage LED Fixture

Type	
Project	
Catalog No.	

## DIMENSIONS



## COMPATIBLE DIMMERS

MANUFACTURER	STYLE	MODEL NUMBER	TYPE
<b>Lutron</b>	Diva	DVCL-153P	(CFL/LED)
	Diva	DVELV-303P	(Electronic Low Voltage)
	Diva	DVLV-600P	(Magnetic Low Voltage)
	Maestro	MACL-153M	(CFL/LED)
	Maestro	MFR2-6DN-120	(Spec Grade)
	Skylark	SELV-300P	(Electronic Low Voltage)
	Skylark	S-600	(Incandescent)
	Skylark Contour	CTCL-153P	(CFL/LED)
<b>Leviton</b>	Acenti	Ate06-1LW	(Electronic Low Voltage)
	Trimatron	705	(Incandescent)
<b>Cooper</b>	Devine	D106P	(Incandescent/Magnet/Low Voltage)
<b>Pass &amp; Seymour</b>	Harmony		(Incandescent 600W)