SP4-xx

MINI FLUORESCENT SLEEK PLUS
T4 • 2-WIRE CLASSIC NON GROUNDED

Type	
Project	
Catalog No.	



CATALOG INFORMATION

MODEL	DIMENSIONS	LAMPING	LUMENS*	COLOR OUTPUT	FINISH
SP4-6**	9-3/8"L x 3/4"W x 1-1/4"H	T4 6W	480	30, 41, 64, BU, GN, RD	W – White
SP4-8	13-1/2"L x 3/4"W x 1-1/4"H	T4 8W	600	30, 41, 64, BU, GN, RD	W – White
SP4-12	17-1/2"L x 3/4"W x 1-1/4"H	T4 12W	800	30, 41, 64, BU, GN, RD	W – White
SP4-16	19-1/2"L x 3/4"W x 1-1/4"H	T4 16W	1000	30, 41, 64, BU, GN, RD	W – White
SP4-20	21"L x 3/4"W x 1-1/4"H	T4 20W	1350	30, 41, 64, BU, GN, RD	W – White
SP4-22	29"L x 3/4"W x 1-1/4"H	T4 22W	1850	30, 41, 64, BU, GN, RD	W – White
SP4-24	34-1/2"L x 3/4"W x 1-1/4"H	T4 24W	2150	30, 41, 64, BU, GN, RD	W – White
SP4-26	40-3/8"L x 3/4"W x 1-1/4"H	T4 24W	2550	30, 41, 64, BU, GN, RD	W – White
SP4-28	46-1/4"L x 3/4"W x 1-1/4"H	T4 28W	2900	30, 41, 64, BU, GN, RD	W – White

* Based on 4100K lamps.
** The 6W fixture is not available with a Rocker Switch. A cord and plug with switch (SP-PCSW) may be ordered separately.

Ordering Instructions	MODEL	SWITCH	/	OUTPUT	–	FINISH	
Examples:	SP4-8	SW	/	30	–	W	With built-in Rocker Switch
	SP4-8		/	30	–	W	Without Rocker Switch

DESCRIPTION

- Sleek Plus T4 fluorescent fixtures are furnished with replaceable lamps, tight-fit direct connectors, stainless steel mounting clips for vertical or horizontal mount, and ribbed acrylic lamp covers.
- Fixtures butt together reducing dark area to less than 1" and with minimal shadowing when they are connected directly.
- Optional On/Off Rocker Switch that does not increase the length of the fixture as it is located on the side.
- Lamp CRI > 82 with the use of tri-phosphor.
- Power and connector cables have separate UL listings.
- Functions with all code approved lighting branch circuits, including 15A and 20A, as the fixtures are not limited to any size circuit. The wiring is according to lighting circuit load ratings.
- The ribbed acrylic diffuser lamp cover fits securely on the housing of the fixture with no light leaks, warping or deformed lens.
- Linkable up to 10 units, max 350 watts.
- Additional power supply cables, connecting cables, hard wire boxes and replacement lamps are sold separately.

COLOR OUTPUT

30 – 3000K
41 – 4100K
64 – 6400K
BU – Blue
GN – Green
RD – Red

LAMPING:
The T4 lamps (included with fixtures) are energy efficient and long-life with a 16,000 hours rating.

BALLAST:
The fixture features a built-in programmed-start, no flickering, silent electronic ballast rated AC 120V 50-60Hz.
3-years commercial grade fluorescent ballast warranty.

CONSTRUCTION:
The housing is made of extruded aluminum with white enamel painted finish. Aluminum provides better heat dissipation, and longer fixture and lamp life.

LISTINGS:
UL &CUL Listed.
New York City approval.
FCC Part 18 Listed – tested for in-line and radiated interference.

ACCESSORIES

FIXTURE	MODEL / DESCRIPTION
	SP-DC: Direct Connector
	SP-B: Plastic Hard Wire Box with Control Switch 3-5/8”L x 2-1/4”W x 1-3/8”H
	SP-BM: Commercial Grade Metal Hard Wire Box**.** Enables fixtures to be controlled by wall switch 2-3/4”L x 1-3/4”W x 1-3/4”H
	SG-MC-VH: Stainless Steel Mounting Clip for Vertical & Horizontal Mount
	SG-MC-V: Stainless Steel Mounting Clip for Vertical Mount
	SG-MC-45: 45°Mounting Clip
	SP-PS6: Power Strip with 12 Outlets**.** Includes (1) Direct Connector (SP-DC) 72”L x 7/8”W x 7/8”H

FIXTURE	MODEL / DESCRIPTION
	SP-CC6: 6” Connecting Cable **SP-CC12:** 12” Connecting Cable **SP-CC24:** 24” Connecting Cable **SP-CC36:** 36” Connecting Cable
	SP-CC6L: 6” Right-Angle Connecting Cable **SP-CC12L: :** 12” Right-Angle Connecting Cable **SP-CC24L:** 24” Right-Angle Connecting Cable **SP-CC36L**: 36” Right-Angle Connecting Cable
	SP-PC72-W: Power Cord & Plug 6’ White
	SP-PCSW: 6’ Power Cord & Plug with Switch
	SP-PCL: 6’ Right Angle Power Cord & Plug – From Back
	SP-PCLL: 6’ Right Angle Power Cord & Plug – From Front