



RS3001R

RECESSED LIGHTING
3" APERTURE LINE VOLTAGE HOUSINGS

Type	
Project	
Catalog No.	




DESCRIPTION

Designed for remodeling applications, this 3" downlight is ideal for accent and task lighting. The housing can be securely mounting into a ceiling up to 5/8" thick with remodeling clips and accepts a 50W GU10 base MR16 lamp. It can be installed in either a damp or dry location but requires at least 3" clearance from ceiling insulation. Available with wide assortment of trims sold separately.

FEATURES

- Galvanized steel housing
- 3" line voltage remodel Non-IC, Non-Airtight universal housing
- Thermal protector protects against overheating from improper lamping or insulation
- 3 remodeling clips secure housing and can accommodate a ceiling thickness of upto 5/8" thick.
- Ceramic socket with aluminum heat shield for 120V MR16 with GU10 base.
- ETL listed for damp locations

SPECIFICATIONS

Model	RS30001R
Input Voltage	120 VAC
Wattage Max	50 W
Dimming	With line voltage incandescent dimmer
Dimensions	12" L x 1-3/4" W x 4" H
Cut-Out	3-1/4" Ø
Environment	Indoor, Damp
Certifications	
Warranty	5 Years – see published warranty terms for detailed information.

ORDERING INFORMATION

MODEL
RS3001R