

ENVISAGE V

LED CEILING & ADA WALL



THIRD EDITION


JESCO
LIGHTING GROUP

JESCO Lighting presents a new line of Envisage Ceiling and ADA Wall fixtures. A portion of the offering incorporates our new AC driverless line voltage LEDs. These state-of-the-art LED modules offer a very high lumen output while providing beautifully even illumination. The AC LED technology does not require the use of any driver, thereby eliminating the weakest link in the LED system and extending the life of the fixture, providing a 5-year warranty.

The CM405 is a uniquely versatile fixture. Available in two sizes with a polycarbonate lens, it can be used as a low wattage, energy efficient ceiling fixture for use in residential homes, apartments or condominium hallways, closets, pantries, laundry rooms, utility rooms, garage applications, offices as well as damp and indoor wet locations such as showers.

The CM405, with an integrated line voltage LED source, can also quickly and easily be converted into a low-profile downlight retrofit trim with the addition of a conversion mounting kit. The fixture fits most existing 4", 5" and 6" downlight housings. With the use of quick-attach clips, the fixture converts a medium-based incandescent downlight to a dimmable, high output, energy saving LED fixture.

All fixtures in this collection offer a broad range of minimalist contemporary designs for any commercial, institutional and residential applications.

APPLICATIONS:

- Homes, condominiums, apartments
- Hotel lobbies, guest rooms
- Office entryways, corridors, meeting rooms, executive offices
- General office work areas, showroom spaces
- Restaurants, bars, private clubs, health spas
- Retail store decorative and general lighting
- Public areas such as airports, bus terminals, railway stations
- Hospital and clinic waiting areas, workstations, exam rooms, offices





ENVISAGE • AC LED • CEILING & WALL



Shown in White



Shown in White
ADA Compliant

ROUND FLUSH MOUNT WITH POLYCARBONATE LENS
Ceiling and ADA Wall Mount or Downlight Retrofit
Line Voltage LED

CM405



CM405R



Dimming: 10-100% Triac, ELV, MLV, CFL/LED
Environment: Indoor - Dry, Damp, Wet
LED Life: 50,000 hours

Model	Size	Watts	Lm*	Lm/W
CM405 S	6" Ø x 1 1/4"H	12W	883	69.4
CM405R S			620	48
CM405 M	7 3/8" Ø x 1 1/4"H	15W	1086	72.4
CM405R M			863	58

* Based on 3000K

TO ORDER CM405

MODEL	SIZE	CCT/CRI	FINISH
CM405	S - 4" Ø	2790 - 2700K 90CRI	WH - White
		4090 - 4000K 90CRI	
		4090 - 4000K 90CRI	
M - 6" Ø		3080 - 3000K 80CRI	CH - Chrome
		4080 - 4000K 80CRI	
		2780 - 2700K 80CRI	
3080 - 3000K 80CRI			
2780 - 2700K 80CRI	BN - Brushed Nickel		
4090 - 4000K 90CRI			
			2780 - 2700K 80CRI
	4080 - 4000K 80CRI		
	3090 - 3000K 90CRI		

CM405R	S - 4" Ø		
		4090 - 4000K 90CRI	



CONVERT AN EXISTING INCANDESCENT RECESSED DOWNLIGHT INTO A DIMMABLE, HIGH OUTPUT, ENERGY SAVING LED FIXTURE IN MINUTES

The CM405 is a unique fixture. Designed for ceiling and ADA compliant wall applications, this versatile fixture also works as a retrofit unit for existing recessed downlights.

Available in small or medium, the low 1 1/4" profile CM405 quickly converts an existing high-wattage incandescent recessed downlight into an energy efficient, long-life AC LED fixture with the addition of a simple mounting kit.

The Small CM405 is compatible with most existing 4" New Construction or Remodel Incandescent Recessed Downlights whereas the Medium CM405 will work with most 5" or 6" housings.

The mounting kit includes torsion springs or spring clips that secure the CM405 into the downlight housing. Also included is a special socket adapter that connects the original Edison-based socket from the downlight to the CM405 Light Disk.

Suitable for retrofit with both new construction and remodel ceiling applications in residential dwellings, kitchens, hallways, closets, pantries, laundry rooms, utility rooms, garages, offices and damp locations such as bathrooms.



ACCESSORIES



CM405S-MK
Retrofit kit for Small CM405
Compatible with most 4" Incandescent Recessed Downlights
Includes Retention Bracket and E26 Adapter



CM405M-MK
Retrofit kit for Medium CM405
Compatible with most 5" or 6" Incandescent Recessed Downlights
Includes Retention Bracket and E26 Adapter

- 1** The special adapter connects the Medium-based socket from the existing downlight housing to the CM405 Light Disk.
- 2** Retention clips mount to the back of the CM405 Light Disk and secure fixture into downlight housing.

ENVISAGE • AC LED • CEILING & WALL



Shown in Brushed Nickel



Shown in White

Shown in Chrome



ADA Compliant

CM403P CONTEMPORARY ROUND ACRYLIC LENS WITH CONCENTRIC RINGS

Ceiling Mount
Line Voltage LED



CM403 CONTEMPORARY ROUND GLASS WITH CONCENTRIC RINGS

Ceiling Mount
Line Voltage LED



Dimming: 10-100% Triac, ELV, MLV, CFL/LED
LED Life: 50,000 hours

Model	Size	Watts	Lm*	Lm/W
CM403 S CM403P S	11 7/8" Ø x 3 1/2" H	15W	990	66.0
CM403 M CM403P M	14 1/2" Ø x 4" H	23W	1490	64.7

* Based on 3000K, 80 CRI
** Energy Star - 90CRI only

TO ORDER

MODEL	SIZE	- CCT/CRI	- FINISH
CM403P	<input type="text"/>	- <input type="text"/>	- <input type="text"/>
	S - 11 7/8" Ø	2790 - 2700K 90CRI	BN - Brushed Nickel
	M - 14 1/2" Ø	3090 - 3000K 90CRI	
		4090 - 4000K 90CRI	
CM403	<input type="text"/>	- <input type="text"/>	- <input type="text"/>
	S - 11 7/8" Ø	3080 - 3000K 80CRI	WH - White
	M - 14 1/2" Ø	4080 - 4000K 80CRI	



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



Shown in Brushed Nickel



ADA Compliant



Shown in Brushed Aluminum

Shown in White

CM402

CLASSIC ROUND WITH ACRYLIC LENS AND METAL TRIM

Ceiling and ADA Wall Mount
Line Voltage LED



Dimming: 10-100% Triac, ELV, MLV, CFL/LED

LED Life: 50,000 hours

Model	Size	Watts	Lm*	Lm/W
CM402 S	11 3/8" Ø x 3 1/2"H	15W	1000	66.7
CM402 M	14 3/8" Ø x 3 7/8"H	23W	1420	61.7

* Based on 3000K, 80 CRI
** Energy Star - 90CRI only

TO ORDER

MODEL	SIZE	- CCT/CRI	- FINISH
CM402	S - 11 3/8" Ø	2790 - 2700K 90CRI	BN - Brushed Nickel
		3090 - 3000K 90CRI	
		4090 - 4000K 90CRI	
M - 14 3/8" Ø		3080 - 3000K 80CRI	BA - Brushed Aluminum
			WH - White
		2790 - 2700K 90CRI	BN - Brushed Nickel
		3090 - 3000K 90CRI	
		4090 - 4000K 90CRI	
		3080 - 3000K 80CRI	WH - White
		4080 - 4000K 80CRI	

ENVISAGE • AC LED • CEILING & WALL



ADA Compliant

CM401

CLASSIC SQUARE WITH ACRYLIC LENS

Ceiling and ADA Wall Mount
Line Voltage LED



Dimming: 10-100% Triac, ELV, MLV, CFL/LED
LED Life: 50,000 hours

Model	Size	Watts	Lm*	Lm/W
CM401 S	11" L x 11" W x 2 1/2" H	15W	976	65.1
CM401 M	14" L x 14" W x 3" H	23W	1369	59.5

* Based on 3000K, 80 CRI
** Energy Star - 90CRI only

TO ORDER

MODEL	SIZE	CCT/CRI	FINISH
CM401	S - 11"	2790 - 2700K 90CRI	WH - White
		3090 - 3000K 90CRI	
		4090 - 4000K 90CRI	
		3080 - 3000K 80CRI	
M - 14"	2790 - 2700K 90CRI		
	3090 - 3000K 90CRI		
	4090 - 4000K 90CRI		



ADA Compliant



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

CM406

CLASSIC DOME WITH ACRYLIC LENS

Ceiling and Wall Mount
Line Voltage LED



Dimming: 10-100% Triac, ELV, MLV, CFL/LED
LED Life: 50,000 hours

Model	Size	Watts	Lm*	Lm/W
CM406 S	11 13/16" Ø x 3 17/32" H	15W	1050	70.0
CM406 M	14 13/16" Ø x 4 1/8" H	23W	1490	64.8

* Based on 3000K, 80 CRI
** Energy Star - 90CRI only

TO ORDER

MODEL	SIZE	- CCT/CRI	- FINISH
CM406	<input type="text"/>	<input type="text"/>	<input type="text"/>
	S - 11 13/16"	2790 - 2700K 90CRI 3090 - 3000K 90CRI 4090 - 4000K 90CRI 3080 - 3000K 80CRI 4080 - 4000K 80CRI	WH - White
	M - 14 13/16"	2790 - 2700K 90CRI 3090 - 3000K 90CRI 4090 - 4000K 90CRI	





CM406 shown

ENVISAGE • AC LED • CEILING & WALL



The RE-GEO-FM-900 offers a cost effective solution for general lighting in residential and commercial applications. Incorporating JESCO's AC LED technology, the fixture eliminates the use of drivers - the weakest part of the LED system - guaranteeing a long lifetime. The white acrylic diffuser provides uniform lighting that can be mounted horizontally or vertically in any room. With the ADA compliant design, it can also be used in hallways and stairwells. Available in 3 sizes - 24", 36" and 48", all providing an efficacy of 70 Lm/W and suitable for use in dry or damp locations. All sizes are dimmable with most standard Triac and CFL/LED dimmers.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



RE-GEO-FM-900

LED VANITY & CEILING LIGHT



Dimming: Triac, CFL/LED

LED Life: 50,000 hours

Model	Size	Watts	Lm*	Lm/W
RE-GEO-FM-900 24	24" L x 6" W x 3" H	20W	1400	70
RE-GEO-FM-900 36	36" L x 6" W x 3" H	30W	2100	70
RE-GEO-FM-900 48	48" L x 6" W x 3" H	40W	2800	70

* Lumen data based on 2700K, 90 CRI

** Energy Star - 90CRI only

† Custom option. Consult factory.

TO ORDER

MODEL	SIZE	CCT/CRI	FINISH
RE-GEO-FM-900			
	24 - 24"	2790 - 2700K 90CRI	WH - White
	36 - 36"	3080 - 3000K 80CRI	
	48 - 48"	3580 - 3500K 80CRI	



ENVISAGE • LINE VOLTAGE • LED DISK LIGHT



The RE-GEO-FM-991 LED Disk Light is available in a domed die-cast configuration providing an easy and cost effective solution to the traditional flush mounted ceiling light. Easily mounts on to standard junction boxes or may be used to retrofit 4" and 6" recessed incandescent housings with the included mounting kit. These fixtures are designed for damp or dry locations and are dimmable down to 10% with Triac or CFL/LED dimmers.



RE-GEO-FM-991

LED DISK LIGHT



Dimming: Triac, CFL/LED

Beam: 115°

LED Life: 50,000 hours

Model	Size	Watts	Lm*	Lm/W
RE-GEO-FM-991 04	5 7/8" Ø x 1" H	8W	650	81
RE-GEO-FM-991 06	7 3/8" Ø x 1 1/2" H	10W	750	75

* Lumen data based on 3000K, 80 CRI

TO ORDER

MODEL	SIZE	CCT/CRI	FINISH
RE-GEO-FM-991			
	04 - 5 7/8" Ø	2790 - 2700K 90CRI	WH - White
	06 - 7 3/8" Ø	3080 - 3000K 80CRI	
		3580 - 3500K 80CRI	

INCLUDED ACCESSORIES



4" Disk Light shown assembled with Downlight Retrofit parts (Included in box)



6" Disk Light shown assembled with Downlight Retrofit parts (Included in box)

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

The RE-GEO-FM-992 LED Disk Light is available in a recessed configuration with a multi-groove design providing an easy and cost effective solution to the traditional flush mounted ceiling light. Easily mounts on to standard junction boxes or may be used to retrofit 4" and 6" recessed incandescent housings with the included mounting kit. These fixtures are designed for damp or dry locations and are dimmable down to 10% with Triac or CFL/LED dimmers.



WARNING: Cancer and Reproductive Harm - www.P66Warnings.ca.gov

RE-GEO-FM-992

LED DISK LIGHT



Dimming: Triac, CFL/LED

Beam: 110°

LED Life: 50,000 hours

Model	Size	Watts	Lm*	Lm/W
RE-GEO-FM-992 04	5 3/8" Ø x 1 1/2" H	8W	650	81
RE-GEO-FM-992 06	7 3/8" Ø x 1 1/2" H	10W	750	75

* Lumen data based on 3000K, 80 CRI

TO ORDER

MODEL	SIZE	CCT/CRI	FINISH
RE-GEO-FM-992			
	04 - 5 3/8" Ø	2790 - 2700K 90CRI	WH - White
	06 - 7 3/8" Ø	3080 - 3000K 80CRI	
		3580 - 3500K 80CRI	

INCLUDED ACCESSORIES



ENVISAGE • LINE VOLTAGE • CEILING & WALL



The RE-GEO-FM-910 square low-profile ceiling fixture offers a cost effective solution for general lighting in both residential and light commercial applications. Available in 11" and 14" sizes, the white acrylic diffuser is easily removed with hidden latches for easy installation in any room. Applications include bedrooms, kitchens, foyers, hallways and offices. Both sizes incorporate a highly efficient LED design providing up to 73 lumens per watt which is dimmable down to 10% with most Triac or CFL/LED type dimmers. Suitable for use in dry or damp locations.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



RE-GEO-FM-910

LED CEILING SQUARE DRUM



Dimming: Triac, CFL/LED

LED Life: 50,000 hours

Model	Size	Watts	Lm*	Lm/W
RE-GEO-FM-910 11	10 7/8" x 10 7/8" x 3 1/4"	15W	1100	73
RE-GEO-FM-910 14	13 7/8" x 13 7/8" x 3 1/4"	25W	1800	72

* Lumen data based on 3000K, 80 CRI

TO ORDER

MODEL	SIZE	CCT/CRI	FINISH
RE-GEO-FM-910			
	11 - 10 7/8" Square	2790 - 2700K 90CRI 3080 - 3000K 80CRI	WH - White
	14 - 13 7/8" Square	3580 - 3500K 80CRI	

The RE-GEO-FM-930 is a round, low-profile ceiling fixture offering a cost effective solution for general lighting in both residential and light commercial applications. Available in 11" and 14" diameters, the white acrylic diffuser is easily removed for quick installation in any room. Applications include bedrooms, kitchens, foyers, hallways and offices. Both sizes incorporate a highly efficient LED design providing up to 70 lumens per watt which is dimmable down to 10% with most Triac or CFL/LED type dimmers. Suitable for use in dry or damp locations.



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



ADA Compliant



RE-GEO-FM-930

LED CEILING ROUND DRUM



Dimming: Triac, CFL/LED
LED Life: 50,000 hours

Model	Size	Watts	Lm*	Lm/W
RE-GEO-FM-930 11	11 1/2" Ø x 3" H	15W	950	63
RE-GEO-FM-930 14	13 5/8" Ø x 3 1/2" H	25W	1750	70

* Lumen data based on 3000K, 80 CRI

TO ORDER

MODEL	SIZE	CCT/CRI	FINISH
RE-GEO-FM-930	11 - 11 1/2" Ø 14 - 13 5/8" Ø	2790 - 2700K 90CRI 3080 - 3000K 80CRI 3580 - 3500K 80CRI	WH - White

ENVISAGE • LINE VOLTAGE • CEILING & WALL



The RE-GEO-FM-940 is a round domed ceiling fixture offering a cost effective solution for general lighting in both residential and light commercial applications. Available in 11" and 14" diameters, the white acrylic diffuser is easily removed for installation in any room. Applications include bedrooms, kitchens, foyers, hallways and offices. Both sizes incorporate a highly efficient LED design providing up to 73 lumens per watt, dimmable down to 10% with most Triac or CFL/LED dimmers. Suitable for use in dry or damp locations.



RE-GEO-FM-940 LED CEILING ROUND MUSHROOM



Dimming: Triac, CFL/LED
LED Life: 50,000 hours

Model	Size	Watts	Lm*	Lm/W
RE-GEO-FM-940 11	10 5/8" Ø x 3 1/4" H	15W	1050	73
RE-GEO-FM-940 14	13 1/8" Ø x 3 3/4" H	25W	1800	72

* Lumen data based on 3000K, 80 CRI

TO ORDER

MODEL	SIZE	CCT/CRI	FINISH
RE-GEO-FM-940	11 - 10 5/8" Ø 14 - 13 1/8" Ø	2790 - 2700K 90CRI 3080 - 3000K 80CRI 3580 - 3500K 80CRI	WH - White

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov





For more details and product specifications please visit
JESCOLIGHTING.COM



NEW YORK
CORPORATE OFFICE
15 Harbor Park Drive
Port Washington NY 11050
TEL 800 527 7796
FAX 855 265 5768

LOS ANGELES
219 South 6th Avenue
City Of Industry CA 91746
TEL 626 333 3661
TEL 855 654 0110
FAX 626 333 2955

DALLAS SHOWROOM
Dallas Trade Mart
Showroom TM 4313
2100 N. Stemmons Freeway
Dallas TX 75207

JESCOLIGHTING.COM
info@jescolighting.com

© 2018 JESCO LIGHTING

LCAT-ENVISAGE-5-3

