

NEO SLIM
DUAL-BENDING
24V OUTDOOR FLEXIBLE LED



NEO SLIM DUAL-BENDING OUTDOOR FLEXIBLE LED



DL-FLEX2-LNDBSL

NEO DUAL-BENDING SLIM
OUTDOOR FLEXIBLE LED

LED	24V DC	2.4 W/Ft	210 Lm/Ft	86 Lm/W	90+ CRI
DIM	120°	WET	IP65	UL LISTED	

Dimensions	3/8" W x 3/8" H (10 x10mm)
Max/Min Run	16' 4" / 4" (nominal)
Dimming*	0-10V, MLV, ELV, TRIAC, CL, PWM, TUYA, CASAMBI ready
Environment	Indoor/Outdoor Dry, Damp & Wet

TO ORDER

MODEL	CCT/CRI
DL-FLEX2-LNDBSL -	<input type="text"/>
	2790 - 2700K 90CRI
	3090 - 3000K 90CRI
	4090 - 4000K 90CRI

* Must be paired with compatible JESCO dimmable driver or controller. Product Lumen Output and Lumens/Watt are based on 4000K color temperature. Specifications subject to change without notice. See spec sheet or jescolighting.com for more details.

JESCO Lighting's FLEX2 **NEO Slim** mimics the aesthetics of traditional neon lighting. Its unique construction, with non-pixelated light diffusion, enables the product to be freely bent in any direction, vertically and horizontally. The product is IP65 rated for both indoor and outdoor applications. Multiple wiring methods available.




DL-FLEX2-LNDBSL



DL-FLEX2-LNDBSL
Shown with Endcap



DL-FLEX2-LNDBSL
Cross-section



DL-FLEX2-LNDBSL
Shown with Metal
Mounting Bracket

TERMINATION FACTORY SEALED



DL-FLEX2-LNDBSL-TS-PC-HW
Tail-Side Connector with Hardwire Leads



DL-FLEX2-LNDBSL-US-PC-HW
Universal Side Connector with Hardwire Leads



DL-FLEX2-LNDBSL-EC
Endcap



SEALANT
Seal endcap to product post field shortening


MOUNTING OPTIONS



DL-FLEX2-LNDBSL-BR
Metal Mounting Bracket



DL-FLEX2-LNDBSL-CH3
3' Metal Mounting Channel



DL-FLEX2-LNDBSL-CH3-BEND
3' Metal Bendable Channel