

E-SERIES FIRE RATED REGRESSED DOWNLIGHTS



4" FIRE RATED E SERIES REGRESSED DOWNLIGHT

RLF-E4FR

4" FIRE RATED E-SERIES REGRESSED DOWNLIGHT

3 SDCM	90+ CRI	120V 277V	15W	1151 Lm	77 Lm/W	
IC RATED	AIR TIGHT		WET			

Dimming	TRIAC, 0-10V
CCT	2700K/3000K/3500K/4000K/5000K - Switchable
Beam	38°, 20°, 65°
Dimensions	4 1/2" Ø x 3 3/4" H
Cut-Out	3 3/4" Ø
Ratings	IC, Airtight Code compliant for use in fire-rated constructions up to a maximum of 2-hours

Lumen data based on 4000K 90CRI, 38° optics.
Specifications subject to change without notice.
See spec sheet or jescolighting.com for more details.



JESCO introduces the **E Series Fire-Rated Downlights**, an innovative lighting solution engineered to meet the highest safety standards. Designed for fire-rated assemblies, these 4" downlights provide up to 2 hours of fire resistance, ensuring compliance with stringent building codes. Ideal for residential, commercial, and institutional installations.



5-Way CCT Selectable Switch is located on Junction Box

OPTIONS



RLH-23354-NC-UNI
New Construction Mounting Plate With Hanger Bars.



RLF-EX2-CC10
E Series 2-Pins Extension Cable
Length: 10'



EM-LIN-25W
25W Remote Mounted
Emergency Battery

TO ORDER

SERIES	MODEL	POWER	TRIM	BEAM	FINISH
RLF-E4	FR	15W			
RLF-E4 - 4" E-Series Downlight	FR - Fire Resistant	15W - 15 Watt	RD - Round Trim SD - Square Trim	NF - 20° FL - 38° WF - 65°	BK - Black Trim WH - White Trim